

GLION SNAPnGO User Manual Model No. 325

Stop and read the Limited Warranty at the end of this User Manual before proceeding any further. If you disagree with any of the terms and conditions of the Limited Warranty, you must submit a written request to support@glion-scooter.com for a Return Authorization within 3 days of delivery. Do not unpack or assemble the SNAPnGO. The scooter must be returned in its original box and in new and unused condition, accompanied by the original receipt. The scooter serial number is engraved on the bottom of the scooter neck. Use the serial number and register your warranty on www.glion-scooter.com

SNAPnGO User Manual Model No. 325

Thank you for purchasing a SNAPnGO Electric Scooter by Probity Cell LLC doing business as GLION Electric Scooter. For your safety and the reliable operation of this product, please carefully read this User Manual in its entirety AND VIEW INSTRUCTIONAL VIDEOS on our website BEFORE operating this product. The information in this manual is accurate as of the time of printing. To determine whether updates have been added, please visit our website (glion-scooter.com) for the latest version of the User Manual. The website also provides videos demonstrating how to fold, unfold, and operate the scooter. Your SNAPnGO Electric Scooter is covered by a warranty. For the specifics of this warranty, visit our website at www.glion-scooter.com. Please register your SNAPnGO Electric Scooter at www.glion-scooter.com for warranty coverage.

Please do not hesitate to contact us if you have any questions:

support@glion-scooter.com

www.glion-scooter.com Probity Cell LLC 701 4th Avenue, Suite 7 Holdrege, NE 68949 855-500-2640



A mobility scooter is not a toy. It is an electrically powered scooter and failure to follow safe operating procedures and safety warnings at all times could result in serious personal injury or death in addition to the injury or death of others.

Driving a mobility scooter requires a combination of healthy traits and abilities, including but not limited to: good vision; strength; coordination; balance and concentration. If you have these traits and abilities, you are on the right track. Additionally, to safely operate the SNAPnGO, you must be able to:

- Read and understand all SNAPnGO reference materials, including this Users Instruction Manual and all SNAPnGO safety instructions contained in this Manual.
- Stand and walk independently or with limited assistance.
- Have sufficient hand strength to operate the throttle and brake.
- Maintain and shift balance to accommodate inclines, declines and turns as described in this User Manual and other SNAPnGO safety instructions.
- Steer and control the mobility scooter.
- See pedestrians and vehicles.
- Judge speeds, distances and slopes.
- Recognize hazards and obstacles in your path.
- Be patient enough to slow down, stop and wait whenever necessary.
- Mount or dismount the mobility scooter without assistance or risk of falling.
- Easily get the mobility scooter in and out of its storage place.
- Use both hands on the handlebars.



TABLE OF CONTENTS

SAFETY SPECIFICATIONS AND OWNER OBLIGATIONS	4
GLĪON SNAPNGO MODEL 315 SPECIFICATIONS	
GLĪON MODEL 325 PARTS DIAGRAM	c
FOOT PEDAL INSTALLATION	10
UNFOLD/FOLD INSTRUCTIONS	11
VERTICAL SELF STANDING INSTRUCTIONS	
SEAT INSTALLATION	13
BASKET INSTALLATION	15
OVERVIEW OF YOUR SNAPnGO ELECTRIC SCOOTER	16
OPERATING YOUR SNAPnGO ELECTRIC SCOOTER	
ADDITIONAL CONFIGURATION CHANGE USING LCD SCREEN	22
BATTERY AND CHARGER	
GENERAL TROUBLESHOOTING	32
CLEANING, STORING, AND SERVICING	
PRODUCT REGISTRATION	34
GLĪON SNAPnGO LIMITED WARRANTY	34

SAFETY SPECIFICATIONS AND OWNER OBLIGATIONS

- 1. **SAFETY INSTRUCTIONS.** The below instructions and tips will help you to operate your SNAPnGO safely. PLEASE NOTE The SNAPnGO scooter is designed to be used by one person at a time and is not recommended for any person younger than 16 years old.
- Read this Manual and all safety and training instructions and all warning labels before operating the SNAPnGO.
- Do not carry passengers or exceed the maximum weight capacity.
- Do not mount or dismount the SNAPnGO unless it is resting at a complete stop, on a level surface, parking brake engaged and is turned off.
- Comply with all local laws and regulations while operating the SNAPnGO.
- Check that all folding levers and clamps are securely locked before use.
- Always slow down before changing directions and turning.
- Always keep your feet on the foot rests when driving the SNAPnGO.
- Always approach small obstacles straight on and at slow speeds. Do not attempt to drive over curbs, potholes, puddles or any other road hazards. Use common sense when operating the SNAPnGO. Reckless driving can result in an accident!

2. SAFE OPERATING CONDITIONS:

- Do not operate this scooter in traffic.
- Be very careful with inclines. Read below sections for details
- Do not operate this scooter on surfaces that are wet, frozen, oily, or unpaved.
- Never carry passengers or objects that can hinder your ability to safely operate this scooter
- Never use headphones or a cell phone to talk or text while riding.
- Do not exceed the maximum weight capacity.
- 3. **PREGNANT OPERATORS**: Pregnant women should not operate this scooter.
- 4. **DRIVING IMPAIRED:** Never use alcohol or drugs before or while operating this scooter. The use of such hinders your ability to safely operate the scooter.
- 5. **STUNTS:** This scooter is not designed for stunts or tricks and should not be used as such. High speeds, jumps, wheelies, and other trick maneuvers are dangerous and can result in loss of control, accidents, and injury/death to self or others.

6. **INCLINES:** Never operate this scooter on steep inclines (inclines that have slopes steeper than a standard handicap ramp). Always climb and descend inclines straight on and at slow speeds. When climbing inclines, you may need to use higher Gears (gear 3) to allow more power to the motor and maintain your speed depending on the steepness of the hill and rider weight so that the scooter does not loose momentum. If the scooter loses momentum and comes to a stop on an uphill, quickly apply the hand brake and put both feet on the ground. Get off the SNAPnGO and walk the product either up or down the incline. **The scooter has a short wheel base and a high center of gravity. It may become unsteady at excessive speeds. Avoid excessive speeds that can be associated with downhill rides.** When going downhill, always actuate the brakes to control the speed. The brake has an electronic brake. The scooter must be turned on for it to work. The scooter also has a mechanical brake. Always turn the power switch on to enable the electronic brake and check the brake BEFORE beginning to go downhill. Never go downhill without brake being enabled.

WARNING: Failure to control your speed or attempting a sharp turn when descending a hill can result in serious injury or death.

7. **GUEST USE:** Never permit a guest to use this scooter unless the guest has read the user manual and all the warnings. Never allow more than one person at a time to ride the scooter. Never exceed the maximum weight capacity.

WARNING: This product should not be used by persons unwilling or unable to take responsibility for their own actions.

- 8. **INSURANCE:** YOUR INSURANCE POLICIES MAY NOT PROVIDE COVERAGE FOR ACCIDENTS INVOLVING THE USE OF THIS SCOOTER. TO DETERMINE IF COVERAGE IS PROVIDED, CONTACT YOUR INSURANCE COMPANY OR AGENT **BEFORE** USING THE SCOOTER.
- 9. **OPERATOR AGE:** Do not allow anyone under the age of 16 to operate this scooter. This scooter is designed for operation by and the transport of only one person age 16 or older.
- 10. **SURROUNDINGS**: Ride your scooter in a controlled environment away from vehicles, obstacles, and other hazards. Never operate the scooter near steps or swimming pools. Do not drive the scooter on grass, gravel, or any other textured or bumpy surface.
- 11. **INTENDED USE:** This scooter is not designed or intended for stunt tricks, including but not limited to jumps, back wheel wheelies, front wheel wheelies, or operating while standing on the scooter. Always stay seated, keep both hands on the handlebar, both feet on the foot pedal and all three wheels touching the ground while operating the scooter.
- 12. **SPEED:** The scooter's maximum speed is approximately 12 kmh (7 mph) at Gear 3 also gives the scooter the most torque or power for climbing inclines. For your safety, use Gear 1 (under 3kmh or 2mph) for flat surface driving, and be careful to control your speed when

descending hills or turning. The scooter has a short wheel base and can become unsteady at excessive downhill speeds or sharp turns. Do not use Gear 2 (8kmh or 5mph) or Gear 3 while making turns.

13. **VISIBILITY:** Do not ride your scooter at night or in conditions of poor visibility. If riding in such conditions is unavoidable, drive slowly, turning on the lights and wear reflective clothing or vest.

WARNING: Riding at dawn, dusk, or at times of poor visibility without a lighting system that meets state and local laws, and without approved reflectors, is illegal, dangerous, and can result in serious injury or death.

- 14. **TEMPERATURE**: Do not use the scooter when the temperature is below -5 C (23 degrees F).
- 15. **WEATHER CONDITIONS:** Avoid riding in wet or icy conditions. Stop the scooter and walk it across rough or slippery road conditions.

WARNING: Wet or icy weather impairs traction, braking, and visibility for riders and other vehicles and pedestrians sharing the roads. The risk of accident is dramatically increased in wet or icy conditions.

- 16. **SURFACE CONDITIONS:** The scooter is intended for use on hard, flat, dry paved surfaces without loose debris such as sand, leaves, rocks or gravel. Wet, slick, bumps, uneven or rough surfaces may impair traction and contribute to possible accidents. **Do not ride your scooter in mud, grass, gravel, sand, ice, or water. Watch out for potential obstacles that could catch your wheel or force you to swerve suddenly or lose control. Avoid sharp bumps, drainage grates and sudden surface changes.** Stop the scooter and carefully walk it across rough or slippery road conditions.
- 17. **WATER RESISTANCE:** Although some water resistance measures have been made, riding the scooter through standing water, rain, wet or muddy conditions runs the risk of severely damaging it. Do not immerse the scooter in water or directly spray the scooter when cleaning. When parked outside where rain is possible, cover the handlebar controls with water resistant materials to protect the electric controls.
- 18. **SAFETY WHEN NOT RIDING**: When the scooter is not being used for riding, place it in a safe stable and secured environment, keep it away from fire, water and other hazards. When the scooter is in its upright vertical self standing mode, especially in moving public transportation or other crowded space, pay attention to its stability as accidental tipping-over could cause personal

injury as well as damage to the scooter. Always hold the retractable dolly handle to prevent it from tipping over and falling to the ground.			

GLĪON SNAPNGO MODEL 315 SPECIFICATIONS

	Unfolded Dimension	43x22x35 inch
Size	Folded Dimension	40x22x14 inch
	Frame Net Weight	14 kg (31.3 lb)
	Detachable Battery Weight	1.5 kg (3.3 lb)
	Travel Seat Weight	1.5 kg (3.3 lb)
	Deluxe Seat	5 kg (11 lb)
	Maximum Load	136 KG (300 lb)
Performance	Top Speed (Gear 3)	12 km/h* (7mph)
	Gear 2	7km/h (4mph)
	Gear 3	3-4km/h (2mph)
	Range	21 km* (13 miles)
	Voltage	36V
Battery	Туре	Li-ion Battery
	Capacity	6.4AH
	Туре	Brushless DC Motor
Motor	Rated Output Power	250W
	Input Voltage	100-240V
Charger	Charging time	3.5h

^{*} Top speed and range per charge depends on rider weight, wind speed, temperature, riding style, riding surface, battery condition, and other factors. Actual top speed and range per charge may vary.

GLĪON MODEL 325 PARTS DIAGRAM



Scooter Side View Unfolded With Travel Seat



Scooter Side View Unfolded With Deluxe Chair


FOOT PEDAL INSTALLATION

Take the scooter frame out of box.

Step 1: Stand scooter up vertically on its 2 rear wheels and rear bumper (Vertical Self Standing Position) for easy access before installing the foot pedals. You can find 3 bolt holes on each side of the flanges at the bottom of the neck shown below. Foot pedals are bolted onto the flanges. Please note: there are 2 settings for each foot pedals. The factory default is BACKWARD position. If you prefer to extend your feet more forward while riding, you can adjust to FORWARD position by rebolting the foot pedals to the supporting beams.



Vertical Self Standing



Step 2: Using the wrench, bolts and washers provided, attache the foot pedals to the flanges with the flat washer against the scooter frame and the lock washer between the flat washer and the bolt head.



UNFOLD/FOLD INSTRUCTIONS

For video instructions, please visit our website at glion-scooter.com. We encourage you to view the video instructions prior to unfolding/folding operation to avoid damage to your Glion scooter.

UNFOLDING YOUR SCOOTER:



Step on the folding pedal to release the folding lock and lift the handlebar, push the handlebar forward until you hear a click, which means the folding pin is locked in securely (SNAP and GO).



VERY IMPORTANT: Push the T-bar all the way forward and make sure the folding pin is fully seated in its notch.

FOLDING YOUR SCOOTER:

Make sure the scooter is off. While pushing the T-bar forward a little, put one foot on the folding pedal and press. It should unlock. Let the handle bar fold down till you hear a "click". It should lock into the folding position by itself. Very important: pushing the T-bar forward allows the folding mechanism to release so you can press the folding pedal using your foot. Without pushing the T-bar forward while pressing the folding pedal could damage the folding mechanism.





Push T-bar forward to release the pressure on locking mechanism while stepping on the folding lever. **Note:** No need to use force from foot, just rest the foot on the folding lever until the handle bar folds down.


VERTICAL SELF STANDING INSTRUCTIONS



After you fold the scooter, you can lift the front wheel up and have the scooter stand vertically. In the vertical self-standing position, you can also insert the seat post into the collar on driver's side or hang the deluxe seat onto one of the foot pedals. Then you can dolly the scooter around the same as you would a roller bag suitcase. USER NOTE: When hanging the deluxe seat onto the foot pedal, make sure the seat base side is facing towards handle bar to prevent the scooter fall flat towards the other side.

SEAT INSTALLATION

Your SNAPnGO electric scooter comes with two seat options: Deluxe Seat (Standard) and Travel Seat (Optional). They both share the same seat post. The deluxe seat base comes with three positions to allow various distances from seat to handle bar. Using bolts and seat base in the package to install the ideal position for yourself.



Insert the silver seat post into the scooter seat post and make sure the pin is fully seated in the notch. And then insert the deluxe seat into the silver seat post



Armrest: insert the armrest in to the armrest holder under the seat. Adjust the armrest position to find the most comfortable width and use the knob to securely tighten it. You can raise and lower the armrest if needed.





BASKET INSTALLATION

Your SNAPnGO electric scooter has an optional basket. To install the basket, stand in front of the scooter front wheel and hold the basket upside down to have the hooks face towards the driver and position the hooks in-between the braces for the LCD screen. Then carefully rotate the hooks onto the T-bar and rest the hooks on the T-bar.

After the basket is hooked to the front of the T-bar, close the Velcro band around the handle bar down tube.

Hooks upside down and face the driver



Hooks face front when done

around the

OVERVIEW OF YOUR SNAPNGO ELECTRIC SCOOTER

WARNING: SNAPnGO was designed to make everyday mobility easy. However, there are still certain risks that users should be aware of when operating a SNAPnGO electric scooter such as injury from loss of control, tipping over, collisions or falls. It is your responsibility to learn how to safely ride the SNAPnGO to potentially reduce these risks. Our website and support materials outline the potential hazards of driving the SNAPnGO. Prior to riding the SNAPnGO take time to read and understand all support materials including this User Manual which contains safety instructions. Any questions regarding any information contained in this Manual, our website, any support materials or any other general questions should be sent by email to support@glion-scooter.com or called in to our customer service representatives at (855) 500-2640.

1. **Powering On/Off:** To turn the scooter on or off, you must press and hold for about 2 seconds the on/off switch as shown below **(F)**. The LCD screen lights will indicate the power is on by lighting. If the LCD screen is not lit, the scooter is turned off. The scooter will automatically turn off after five minutes of non-use.



- 2. **Headlight On/Off:** To turn the headlight on or off, you must first turn on the scooter power (F). While the scooter power is on, press and hold the Gear Up button (F1) for 2 seconds, the headlight and rear light should be turned on. Press and hold (F1) one more time, and the headlight will be turned off.
- 3. **Accelerator:** The right thumb control is the accelerator (T1). The further you press the accelerator down, the more energy you will release to the motor. **NOTE**: As a safety

feature, the motor will be in the default "braking" mode when the LCD is on and when the accelerator is not pressed. The Default gear is 1 as shown on the LCD screen G section. The speed for gear 1 is 3-4 kmh or 2 mph. Press the gear up button (F1) once, G section will show 2. Press it again, it will show 3. Gear 2 is 7-8 kmh. Gear 3 is 10-12 kmh. To lower the speed, press the gear down button once (F2). Gear 3 has the most torque and speed. Operate your SNAPnGO at a reasonable speed for both your personal safety and others. CAUTION – Do not make turns at high speeds or on steep inclines. Your SNAPnGO may tip over.

- 4. **Reverse thumb control:** The left thumb control is reverse (T2). It has a top speed of 2-3mph and doesn't not change speed regardless of which gear is on.
- 5. **Brake:** The left brake handle is the mechanical brake **(H)**. The scooter is on electronic braking when power is on and the right accelerator or left accelerator is not pressed. The mechanical brake in the left rear wheel provides added safety for emergency purpose. When actuated, it will cut power supply to the motor. **The electronic brake only works when the scooter is turned on.** In a safe, controlled environment, please familiarize yourself with the braking distance of the scooter at different speeds before operating near intersections, pedestrians and other obstacles.
- 6. **LCD Screen:** To reset the trip duration and distance travelled: Turn on the power, AFTER 5 seconds, hold the gear up $\Lambda(F1)$ and gear down V(F2) button for 2 seconds. The Single Trip Duration (TM) and Single Trip Distance (DST) will blink. Push the on/off button (F) once to clear the previous trip information.



WARNING: For your safety and for the safety of others, please take the time to practice accelerating, turning, braking and familiarize yourself with the scooter's braking distance in an open and safe area before taking your scooter out into the general environment. IT IS YOUR RESPONSIBILITY TO MAINTAIN CONTROL OF YOUR SCOOTER AT ALL TIMES!

OPERATING YOUR SNAPINGO ELECTRIC SCOOTER

Just like learning to drive a car or ride a bicycle, operating any personal transportation device inherently includes risk and takes practice. Therefore, use caution as you practice operating the scooter in various situations. Keep the speed at a reduced level until you're comfortable controlling the scooter. The below instructions and practice steps will teach you to maneuver through doorways, on and off lifts, and up and down ramps.

When preparing for your first ride, select an area that is flat, spacious, and away from traffic and other obstacles. Bring a friend along to help you follow the instructions while you practice. Start driving with the lowest speed. Please refer to the Overview section of this Manual for instructions on the SNAPnGO's three speeds.

Getting Ready:

- 1. <u>Fully charge the battery</u>. For safety reasons, the battery is only 50% charged when shipped from the factory (See on page 22 Battery Charging Instructions Below).
- Choose a controlled environment away from vehicles, obstacles, and other hazards for riding. Even if you have experience with motorized scooters, vehicles, bicycles, etc., you must familiarize yourself with the function, handling, turning, ramp climbing, braking distance, performance, and safety of this scooter in a safe and controlled environment.
- 3. Always check and obey all local laws and regulations. Your insurance policies may or may not provide coverage for accidents involving the use of this motorized scooter. To determine if coverage is provided, check with your insurance company or agent. Do not assume your existing insurance policies provide coverage.
- 4. Unfold the scooter (See Unfolding Instructions above).
- 5. Complete a final roadworthiness safety check before operation.
 - a. Make sure folding mechanism, dolly handle, wheel lug nuts, other nuts, bolts, fasteners, etc., are secure.
 - b. Inspect the frame, fork and handlebars for cracks or broken connections.

Riding the Scooter Powered:

- 1. Install foot pedals, the deluxe seat or travel seat onto the scooter frame. Sit on the seat with both feet rested on the foot pedals.
- 2. Press and hold the on/off button on the right handle about two seconds to turn on the scooter. The LCD in the center of handlebar should be lit when the scooter is turned on.
- 3. With both hands on the handlebar and eyes looking forward, press the right thumb throttle to move forward.
- 4. As the motor begins to slowly propel the scooter forward, practice braking by letting go the right thumb throttle or actuate the left hand brake. The scooter should come to a stop.
- 5. Practice reverse by pressing the left thumb throttle, practice braking by letting go the left thumb throttle or actuate the left hand brake. The scooter should come to a stop.
- 6. Press and hold the Gear Up button for 2 seconds on the right handle to turn on the headlight and tail light. Press and hold the Gear Up button for 2 seconds to turn the lights off.
- 7. Press the Gear Up once to go up to 2nd gear and press the thumb throttle. The scooter should go faster. Press the Gear Down button once to reduce to 1st gear to slow down the scooter. Practice the same for the 3rd gear. Practice the following steps to help you become comfortable with your SNAPnGO.

Practice Steps:

- 1. <u>Learn to use the throttle and brake</u>. With your Left hand, apply pressure to the hand brake. Releasing the hand brake, slowly press the right thumb throttle (throttle) and move the scooter forward five feet. While releasing the throttle, apply the hand brake and come to a complete stop. Repeat this process several times, each time allowing the scooter to venture farther before applying the hand brake to come to a complete stop. **PLEASE NOTE** SNAPnGO is a front-wheel-drive scooter. As a result, fast starts can cause its front wheel to spin, which can be dangerous for drivers. Slowly pressing the accelerator each time you start will help to avoid or reduce this condition.
- 2. <u>Learn to turn</u>. Slowly turn the SNAPnGO by using wide movements. Feel how the scooter reacts to your body weight. Shifting your body weight through the turn will help add stability. As you feel more comfortable, you will be able to make the turns tighter. Always remember to slow down before turning or changing directions. Going too fast through a turn will cause the SNAPnGO to tip over. If the SNAPnGO begins to tip, slow the unit down, back off on the turn and place your feet on the ground.
- 3. <u>Learn to reverse</u>. Prior to engaging reverse (left thumb throttle), turn your head to make sure there are not people or hazards such as curbs, parked cars or walls behind you and then slowly press down on the reverse thumb throttle. Only use the reverse function to move away from an obstacle or back out of an elevator. While in reverse, limit turns or changes in directions.
- 4. Avoid steep inclines and hills. The SNAPnGO is not designed to be driven up or down steep inclines or hills. However, the SNAPnGO should be able to drive up all wheelchair ramps which comply with government standards. Leaning your body forward, which places more weight on the front wheel, will aid the scooter up the ramp. Carefully control your speed on the descent. Avoid making turns while going down a hill.

WARNING: Always ride at speeds you can comfortably and safely control. Take the time to familiarize yourself with the electronic brakes and the distance it takes to come to a complete stop at various speeds. Keep both hands on the handle grips while operating the scooter at all times. Failure to do so could result in serious injury or death.

While riding your SNAPnGO you will encounter many situations which will require that you understand the abilities of your scooter. The SNAPnGO provides reasonable safety on flat and level surfaces but can tip over on uneven, slanted or inclined surfaces. Additionally, certain outdoor and indoor conditions can create situations where caution is advised. The following guidelines will help you when encountering certain situations.

TURNS

Unlike a two wheeled vehicle, the SNAPnGO CANNOT be "leaned" into a curve. Therefore, it is essential to slow down to a reasonably slow speed before initiating a turn. Use extreme caution when turning on slanted or uneven surfaces. Occasionally you may find yourself negotiating a curve or corner too fast and the inner rear wheel starts to lift off the ground. If this happens, immediately reduce your speed, lessen the steering angle and shift your upper body toward the wheel that is lifting off the ground.

INCLINES AND DECLINES

Incline conditions require special attention to avoid mishaps. The SNAPnGO is not designed to go up steep or long inclines. Be aware that not all ramps are constructed according to government standards. The government standard for wheelchair ramps is 1 inch (2.5cm) rise per foot (30cm) (5° incline).

WARNING: An incline that is too steep or long can create a dangerous situation. The scooter can lose momentum causing it to slide backwards down the incline or tip over backwards. It is not recommended to drive the scooter on any ramp, incline or hill that doesn't meet government wheelchair ramp standards.

Tips for driving the SNAPnGO on inclines and declines

- Never travel up or down on an incline that is potentially hazardous such as one that is wet, icy, slippery, has loose gravel, etc.
- Always start an incline at the base of the hill and not at an angle.
- Shift your upper body towards the handlebars to shift weight to the front wheel.
- Slowly twist the throttle to move the scooter forward.
- Never stop the scooter on an incline. Do not zigzag, but travel in a straight line to the top.
- If the scooter loses momentum, quickly apply the hand brake and put both feet on the ground. Get off the SNAPnGO and walk the product either up or down the incline.
- Go very slowly while driving down a ramp. Do not go down the ramp or hill at a side angle. Try to avoid turns while descending. Keep your hand on the brake handle and slowly apply pressure if the scooter picks up too much speed.

CURBS

The SNAPnGO should not be driven over any curb. Apply the brake, turn off the scooter and get off the scooter. Lift or walk the scooter around the curb prior to getting back on.

WARNING: Attempting to drive over a curb can cause the product to tip over backwards resulting in possible injury and will cause damage to the scooter. Also use caution when driving on sidewalks near curbs to avoid one wheel falling off the curb. This will cause the scooter to tip over and can result in serious injury or death.

SPEEDBUMPS AND UNEVEN SURFACES

Generally, the SNAPnGO can handle slightly uneven surfaces. You should approach each at a reduced speed and in a direct frontal position. Please keep in mind that the small wheels cannot roll over objects higher than two inches (5cm) and you may fall if you attempt to do so.

WARNING: Attempting to drive over speed bumps or uneven surfaces can cause the product to tip over backwards and can result in serious injury or death.

POTHOLES AND PUDDLES

Avoid all potholes and deep puddles.

WARNING: Attempting to drive over potholes or uneven surfaces can cause the product to tip over backwards and can result in serioius injury or death.

INDOOR USE

Similar to an electric wheelchair, you are generally permitted to use the SNAPnGO inside of buildings, airports, shopping malls, stores, theaters, etc. Doors can be a challenge when using the SNAPnGO. Approach each door slowly making sure that the rear wheels will make it through the door oppening.

OUTDOOR USE

The SNAPnGO should only be ridden on smooth hard and flat surfaces. It is not designed for off-road conditions. Do not use the SNAPnGO in rain or snow nor drive it through puddles of water. Slightly uneven surfaces should be approached at a reduced speed and in a direct frontal position and may require lifting or walking the scooter around the surface. Please keep in mind that the small wheels cannot roll over objects higher than two inches (5cm) and you may fall if you attempt to do so. You should not tow anything behind the SNAPnGO.

ADDITIONAL CONFIGURATION CHANGE USING LCD SCREEN

Normally user do not need to do any configuration using LCD screen. However, in the case user need to change factory default motor speed/power or change default electric braking power level or set up an electronic locking passcode for the scooter, user need to follow instructions below:

Please be aware that increasing top speed can significantly increase the risk of accidents. User should be very cautious in choosing their own top speed and practicing acceleration, turning, stopping, going up ramp, going down ramp and other scooter operations.

WARNING: Operating scooter at high speeds could result in serious injury or death. Please use caution increasing the top speed.

The LCD Display is made up of 2 major components: 1. LCD screen 2 Control Buttons. The Control Buttons has 3 buttons, Up Arrow or Gear Up (UP), Switch On/Off (SW) and Down Arrow or Gear Down (DOWN).



The SETTING mode has 3 different tiers: **Normal Setting, P value and C value**. Below is a complete instruction of settings for each mode. (Modifying top speed is in Normal Setting and modifying gear 1/reverse gear torque is in C value setting.) **Remember: short press of SW will toggle between values, Up or Down will change values, long press of SW will get out of the mode and long press Up and Down at the same time will change mode.** If there is no operation within 1 minute of getting into SETTING mode, the LCD will automatically leaving SETTING mode and resume OPERATING mode.

Increase the top speed

- 1. Press SW to turn on the scooter
- 2. Within 5 seconds, press and hold Up and Down at the same time for 2 seconds. This will allow user to get into the NORMAL SETTING mode. The speed column on Display will be flashing. The default value is 10kmh. This is the top speed of Gear 3. By increasing top speed of Gear 3, you would also increase the top speed of Gear 2 and Gear 1 as lower gears speed are proportionate to top gear speed
- 3. Short press Up or Down to modify the speed. The highest speed SNAPnGO motor can go is 17 kmh. So increasing the number above 17 would only provide a speed of 17 kmh at maximum.
- 4. After modifying the top speed, you can either press and HOLD the SW to get out of SETTING mode and back into OPERATING mode or you can short press the SW to toggle to the next setting motor wheel size.

Motor wheel size is set at 8 inch. This will **NEVER** change for SNAPnGO. Short press SW to toggle to **km Vs mile** settings. This setting will see speed and distance value flashing. The factory default is miles. Use Up or Down arrow to change it. Switching to KM will also have the temperature measurements set to Centigrade from Fahrenheit.

After modifying the km/mile setting, short press SW once to complete the NORMAL SETTING. The speed and distance flashing should stop. If user needs to get back to the OPERATING mode at this time, simply long press SW. If user needs to get into P mode in the SETTING, press and hold the Up and Down at the same time. P1 will start to flash at the bottom of the screen.

P Mode Values:

All the P mode values are pre-determined by factory and should NEVER be changed by user. In case user inadvertently modified factory default value, below chart provides a reference for user to reset to the factory default value. User needs to toggle through P value by short pressing SW. Please do not press Up or Down while going through P mode.

Setting	Description	Factory Default
P 1	Number of motor magnet steel	30
P 2	Rotation pulse	0
P 3	Power Assist Mode	0
P 4	Acceleration Start Mode	0
P 5	Battery level monitoring	12

C Mode Values

In order to get into C mode value settings, user must toggle through P mode by short pressing SW. At the end of P5 setting, short press SW so that P5 value is no longer flashing. Then long press Up and Down at the same time to get into C mode. C1 will start flashing at the bottom of the screen. Most of the values in C mode are pre-determined by factory and should NEVER be changed. Below chart provides a factory default in case some values are inadvertently modified by user.

Setting	Description	Factory Default Value
C1	Power Assist Sensor Mode (Do not change)	02 /10
C2	Motor Sensor Type (Do not change)	0
C3	Gear Level Default (When turning on scooter, which	1 (Strongly
	gear is the default)	recommend as gear 2
		or 3 is fast and could
		cause accidents if not
		used appropriately)
C4	Acceleration Setting (See details below)	4/33
C5	Controller Maximum Electric Current Level (Do not	00
	change)	
C6	Display Brightness Setting (1-5)	3
C7	Cruise Control Setting (Disabled)	0
C8	Motor Temperature Monitoring (Disabled)	0
C9	Password Locking Control (See details below)	0
C10	Master Reset (Do not change)	n
C11	Display Protocol (Do not change)	0
C12	Controller Minimum Voltage (Do not change)	4
C13	Electric Braking Strength Level (1-5 See below)	5
C14	Power Assist Micro Configuration (Do not change)	2

Remember, long press SW to get out of setting at any time.

Modify Gear 1 and Reverse Gear Speed and Torque

Factory default for Gear 1 is 33% of Gear 3 top speed and torque. Reverse gear has a torque that matches Gear 1 torque. The 33% value could be modified. As a result, the Gear 1 speed and torque, which is also the reverse gear torque could be modified. To modify this % value, you need to follow the setting instruction described below and modify the **C4 factory default settings.**

From P mode, long press Up and Down at the same time to get into C mode. Short press SW to toggle through C1-C3 and reach C4.

C4 has a default value of 4. Do not change that or it will render the scooter dysfunctional. Short press SW to toggle over and the cell right above 4 will start to flash. The default value is 33. It means that Gear 1 will have 33% of the scooter top speed and power. Use Up or Down to modify this value. We strongly recommend not to exceed 55 as high value defeats the purpose of multiple gear settings. If you prefer to start at a high gear, you can modify the setting in C3. Modifying the C4 value will also impact the power/torque supplied to the reverse gear. However, speed of reverse gear is fixed.

Please be aware that increasing gear speed can significantly increase the risk of accidents. User should be very cautious in choosing their own top speed and practicing acceleration, turning, stopping, going up ramp, going down ramp and other scooter operations.

WARNING: Operating scooter at high speeds could result in serious injury or death. Please use caution increasing the top speed.

Password Locking Function

C9 would allow user to set up a password to lock the scooter electronically without using a key. Factory default disabled this function but user can change it as a personal preference. Please remember, if the password is forgotten, then user needs to contact dealer or manufacturer to do a reset because it requires a master LCD display. Once you enable the Password Locking, you need to enter the 3 digit password every time you power on the scooter.

To enable the password, toggle to C9 and use Up button to change value to 1. The the cell above will start flash with a default value of 555. Use Up or Down to change each digit to your preferred password and use SW to toggle. When complete, long press the SW to get out of the setting mode. Turn off the scooter and power the scooter on again. The LCD screen will have a 555 next to the Gear number. Use Up or Down to enter your passcode and use SW to toggle. Once you toggle through the correct passcode, the scooter will work. Otherwise, the scooter motor will not start.

Electric Braking Strength Level

The electric braking is actuated by default when accelerator or reverse control is released. To provide maximum safety, currently it's set to provide the maximum breaking strength. Some user may want to soften the braking experience. Please be aware that modifying electric braking strength can significantly increase the risk of accidents. User should be very cautious in choosing their own electric braking strength and practicing acceleration, turning, stopping, going up ramp, going down ramp and other scooter operations.

WARNING: Adjusting the strength of the electronic brake will affect stopping distance and could lead to serious injury or death.

C13 would allow user to modify the electric braking strength. Toggle to C13 and use Up or Down to change values. 5 being the strongest braking and 1 being the lowest. After modification, long press SW to get out of setting mode.

Other Indicators On Display


The following explains the meaning of other indicators on display. When the scooter is turned on and in operating mode, short press SW to toggle through various values:

TM	Single Trip Time Meter
TTM	Cumulative Trip Time Meter
MXS	Single Trip Maximum Speed
AVS	Single Trip Average Speed
DST	Single Trip Range
ODO	Cumulative Trip Range
VOL	Battery Voltage (42 being the maximum or fully charged, 33 being the
	lowest or empty)

To reset the single trip data (time and range), turn on the scooter. **AFTER** 5 seconds, press and hold Up and Down at the same time. TM and DST will be flashing. Short press SW to reset them to 0. Then long press SW to turn off the scooter.

Parking Brake Instruction

Your SNAPnGO scooter comes with a 2-Level parking brake design. Level 2 is tighter than level 1.



Parking brake is NOT actuated

Squeeze the brake handle and push the stopper in. Parking brake is on

Squeeze the brake handle more and push the stopper in. Parking brake is on Gear 2. Gear 2 provides more stopping power. For maximum stopping power, leave the scooter power on also so that front wheel electric braking is also on.

BATTERY AND CHARGER

Each electric scooter is equipped with a lithium battery and a smart charger designed specifically for each other. **ONLY USE THE CHARGER SUPPLIED BY THE MANUFACTURER TO CHARGE THE SCOOTER.** Do not charge the battery with any other charging system. If the battery or charger is damaged due to improper use, the limited manufacturer warranty shall be void. Do not operate the charger near flammable materials such as carpet. Ensure a dry environment. Never allow the charger or cable to come into contact with water as this may result in electric shock. Never touch the charger or cable with wet hands. Disconnect the charger from the outlet if any fault arises during charging. Always pull the plug, not the cable. Do not allow the charger or cables to be damaged or crushed by sharp edges or heat. The charger supplied with the electric scooter should be regularly examined for damage to the cord, plug, enclosure and other parts. In the event of such damage, the scooter must not be charged until the charger has been repaired or replaced. Unplug the charger and disconnect from the scooter when not in use. As a safety

mechanism, when the charger stops charging because either the battery is full or the charger is disconnected from the scooter, the charger must be reset by unplugging it from the outlet before it will resume charging.

BATTERY:

- 1. Fully charge the battery before first time operation or after a long period of non-usage (see *Instructions For Charging* below). For safety reasons, the battery is only 50% charged when shipped from the factory. The battery is fully charged when the LED light on the charger turns green.
- 2. Always charge the battery in a clean, dry location, free of debris.
- **3.** Charge the battery frequently. The battery can be recharged at any time. Do not think that you need to fully deplete the battery before recharging it. In fact, frequent partial discharge/charge cycles will prolong the battery life vs. full discharge/charge cycles. Tips: For every 10-15 partial discharge, do a full discharge and charge cycle.
- 4. Fully charge the battery before storing the scooter for extended periods.
- 5. When not in use, periodically recharge the battery once every three months.
- 6. Battery damage due to water, collision, improper storage and other non-normal factors is not covered by the limited manufacturer warranty.
- 7. SNAPnGO has 2 charging ports. One on the front controller box and one on the battery itself. The default method is charging via the charge port on the controller box as the battery charge port is connected to the front controller box. When battery is detached from the scooter, use the charge port on the battery to charge.



On/Off Switch

Charge port connector and charging port on battery. Do not disconnect unless battery is detached



8. Detaching the battery: The battery comes with keys (2) to lock and unlock the battery from the scooter frame. **Please keep the spare key in a safe place. Glion does NOT have replacement keys.** Detach the charging port connecter first and then use the key provided to unlock the battery. Slide the battery out of its docking station. You can charge a detached battery using the charge port on the battery.



Connect to Power Outlets



Charger Indicator Light. Blue = Connected to Power Source but not charging, it could mean battery is full or battery is not accepting charging. Green= Near Full. Red=Charging.

Charging Tip to Scooter Charge Port.

CHARGER:

1. The battery is charging when the LED light on the charger is red. When the battery is 100% charged, the light on the charger will go from red to green to blue.

- 2. The provided charger has a built in overcharge protection to prevent the battery from being overcharged.
- 3. Charging time is approximately 3.5 hours for a fully discharged battery.
- 4. Regularly inspect the charger for damage to the cord, plug, enclosure and other parts. In the event of such damage, the charger must not be used until it has been repaired or replaced.
- 5. Unplug the charger from the wall outlet when not in use. As a safety mechanism, when the charger stops charging because either the battery is full or the charger is disconnected from the scooter, the charger must be reset by unplugging it from the wall outlet before it will resume charging.
- 6. Use only the charger supplied with this scooter or a recommended replacement specified by Glīon.

WARNING: Failure to confirm compatibility, properly install, operate and maintain any charger, component or accessory can result in serious injury or death.

INSTRUCTIONS FOR CHARGING:

- 1. Turn the scooter off. Open the charge port rubber protective cover and securely plug the charger into the charge port.
- 2. Plug the charger into the power outlet.
- 3. A solid red light on the charger indicates the battery is charging. A solid green light indicates the battery is fully charged.
- 4. Remove the plug from the power outlet, then remove the charger from the scooter's charging socket. Secure the charge port rubber protective cover.

USAGE:

- 1. You will not damage the battery by riding the scooter until the battery is fully discharged and the scooter motor shuts down.
- 2. Avoid operating the scooter when the battery is hot.

BATTERY LEVEL INDICATOR

- 1. The battery level indicator lights are in the LCD display on the top left corner. When the scooter is turned on, the battery level indicator is on. For the battery level indicator to start to work, the scooter motor needs to be actuated for 5 seconds with passenger load. After the initial motor actuation, indicator will engage.
- 2. Fully filled bar means the battery is 85% fully charged. Less filled bar indicates the battery is approaching empty.
- 3. The battery level indicator is accurate when the motor is **not** engaged. When the scooter is standing still, check the battery level indicator for battery capacity status. Do not check the battery indicator when operating the scooter.

4. **Soft Riding Condition**. When the battery is nearly depleted, a "soft" riding condition can occur. A "soft" riding condition means the scooter can move forward at lower speed but under full speed it shuts down. This occurs because under full speed, a large instant current causes the voltage to drop in the battery reaching the controller stop limit to protect the battery and shutting down the scooter. When this happens, turn the scooter back on and drive the scooter under low speed until you can recharge the battery.

WARNING: Like any mechanical device, an electric scoter and its components are subject to wear and stress. Different materials and mechanisms wear or fatigue from stress at difference rates and have different life cycles. If a component's life cycle is exceeded, the component can suddenly and catastrophically fail, causing serious injury or death to the rider. Scratches, cracks, fraying and discoloration are signs of stress-caused fatigue and indicate that a part is at the end of its useful life and needs to be replaced. While the materials and workmanship of your electric scooter or of individual components may be covered by a warranty for specified period of time by the manufacturer, this is no guarantee that the product will last the term of the warranty. Product life is often related to the kind of riding you do and to the treatment to which you submit your electric scooter.

BATTERY:

When used normally, the lithium battery provided with your scooter should not lose more than 30% of its capacity within the first 500 charging cycles. Average battery life for a properly maintained lithium ion battery is approximately 1,000 charge/discharge cycles. If you notice your travel distance significantly diminished despite having a full charge, it is a sign the lithium ion battery needs to be replaced.

Fully charge the battery before storing the scooter for extended periods. Periodically recharge the battery at least every 3 months during storage. Leaving the battery depleted and un-charged for more than 3 months could permanently damage the battery and is not covered by warranty.

BATTERY DISPOSAL:

Your Glīon product uses lithium ion batteries, which must be recycled or disposed of in an environmentally safe manner. Do not dispose of a lithium ion battery in a fire. The battery may explode. Do not dispose of a lithium ion battery with your household trash. The incineration,

landfilling, or combining a lithium ion battery with your household trash is prohibited in most jurisdictions. Locate a place that collects and recycles lithium ion batteries. To search online, go to www.call2recycle.org and enter your zip code, or if you prefer to locate a place by phone, dial 1-877-2-RECYCLE to find the nearest retailer that collects lithium ion batteries.

MECHANICAL:

Due to vibration, nuts and bolts can become loose. Make sure that all lug nuts, other nuts and bolts are securely fastened and tighten them if necessary. To test: Pick your scooter up 1-2 inches and bounce it off the ground. Do a quick visual and tactile inspection of the whole scooter. Make sure you inspect all visible nuts, bolts, and structural welds. If anything sounds, feels, or looks loose, or shows signs of stress replace or secure them.

STORAGE AND DAILY CARE

- 1. Do not store the scooter in direct sunlight, in damp places, or in temperatures below -5° C (23° F) or above 43° C (110° F).
- 2. Fully charge the battery every three months if not in use.
 - **3.** Keep the scooter clean (See section on Cleaning and Servicing).

GENERAL TROUBLESHOOTING

If you experience problems with your scooter, please refer first the following troubleshooting guide:

Problem: The scooter does not operate.

Possible causes/solutions:

- 1. The scooter is not turned on. **Solution:** Turn on scooter by pressing and holding the on/off button approximately 2 seconds.
- 2. The battery is not charged. **Solution:** Charge Battery.
- 3. The hand brake is inadvertently engaged. **Solution:** Make sure hand brake is not engaged.
- 4. The battery is not locked and secured. **Solution:** Secure battery by locking it to the frame using the key provided.
- 5. The on/off switch on the battery is not off. **Solution:** Turn switch on by pressing straight line side of battery switch down.

Problem: The Scooter Operates Intermittently.

Possible causes/solutions:

- 1. The battery is low on charge causing soft riding condition. See on page 31 of User Manual for description of soft riding condition. **Solution**: Recharge Battery.
- 2. The battery is not locked and secured into its base. **Solution:** Secure battery by locking it to the frame using the key provided.

Problem: Short ride time/runs slow.

Possible causes/solutions:

- 1. Rider weight. **Solution:** Do not exceed 136 kg (300 lbs.) maximum weight limit.
- 2. Riding conditions. **Solution:** Use only on flat, dry surfaces. Avoid inclines and areas with debris on surface.
- 3. Battery not fully charged. **Solution**: Charge battery until full.
- 4. Old/Damaged Battery. **Solution:** Replace Battery. Contact Customer Service on our website: www.glion-scooter.com.

Problem: Motor has clicking noise when it is first started.

Possible causes/solutions:

1. This is normal as clicking noise means the motor is reaching its power limits under the current gear. Since the default gear is 1, which means the lowest power, the motor is producing the maximum power when the scooter moves from speed zero. Once the scooter gets moving or is geared up, the noise will go away.

Problem: Charger LED light stays blue after connecting charger to outlet and battery. Possible causes/solutions:

- 1. Charger needs to be reset. Charger experiencing temporary short circuit. **Solution:** Unplug the charger from the outlet, wait for 40 minutes and plug in again.
- 2. When charging from charge port located below handlebar, charge port cord that connects the battery to the front controller charge port is not plugged into battery.
- 3. Battery fuse is blown. **Solution**: unplug the charger from battery, detach the battery from the scooter, and contact support for instructions.

IF YOU'VE CONSULTED THE TROUBLESHOOTING GUIDE AND ARE STILL HAVING PROBLEMS WITH YOUR SCOOTER, PLEASE CONTACT CUSTOMER SERVICE by phone at 855-500-2640, by email at support@glion-scooter.com or on our website: www.glion-scooter.com. Also visit our website for replacement parts, product support, and instructional videos. Use only replacement parts supplied by Glīon.

CLEANING, STORING, AND SERVICING

- 1. **KEEP YOUR SCOOTER DRY:** Do not ride your scooter in wet conditions unless unavoidable. Dry off your scooter immediately.
- 2. **KEEP YOUR SCOOTER CLEAN:** Remove dust and dirt from your scooter with a wrung-out, damp rag. Dry immediately. Never use solvents. Do not spray your scooter down with water or submerse it.
- 3. **STORAGE:** Battery performance is susceptible to temperature. Do not store your scooter in direct sunlight or in a high temperature environment like inside of your car. Store your

scooter indoors, out of the elements. Room temperature is ideal for storage. Avoid storing the scooter in wet environments. Recharge the battery in full after it has been completely discharged and before storing the scooter for longer periods. Even in storage, please monitor the battery level and recharge the battery fully at least once every 3 months.

4. **SERVICE.** Should your scooter require service, please contact customer service through our website (www.glion-scooter.com). Your satisfaction is our greatest priority! Glion.

PRODUCT REGISTRATION

We encourage you to register your Glion Electric Scooter with us. Registration helps us ensure your continued satisfaction and enables us to contact you with new product instructions. Also, registration and proof of purchase are necessary to make a warranty claim. Please register your Glion Electric Scooter at www.glion-scooter.com/register. Please keep your original proof of purchase in a safe place in the event of a warranty claim. Scooter serial number is located behind the front wheel on the neck of the scooter above the folding mechanism.

WARNING: Please register your electric scooter with us. If you don't, we may not be able to contact you directly with important safety recall information.

GLĪON SNAPnGO LIMITED WARRANTY

Probity Cell LLC, dba Glīon® ("Probity Cell") warrants to the first retail purchaser of this product that it is free from defect in materials and/or workmanship for a period of 12 months from the date of purchase or 1,000 miles, whichever occurs first. This limited warranty does not cover normal wear and tear or any damage, failure or loss caused by improper maintenance, storage or use of the SNAPnGO electric scooter. This limited warranty will be void if the product is ever used in a manner other than for recreation or transportation, modified in any way, or rented.

If a defect exists, Probity Cell will, at its option and to the extent permitted by law either (1) provide components to repair the SNAPnGO using new or refurbished parts at no charge to you; (2) exchange the SNAPnGO with a functionally equivalent product that is new or refurbished; or (3) refund the original purchase price. After repair or replacement, the SNAPnGO/functionally equivalent product will be covered by this limited warranty for the longer of the remainder of the

original limited warranty period, or 90 days after Probity Cell ships the SNAPnGO/functionally equivalent product to you. Probity Cell's responsibility to repair or replace the SNAPnGO, or to refund the purchase price, is your exclusive remedy. This warranty excludes damage caused by abuse, misuse, accidents, unauthorized repairs, alterations, modifications, failure to follow instructions in the User's Instruction Manual and battery Operating Instruction, or other causes that are not defects in materials and workmanship for which Probity Cell is responsible.

This Limited Warranty does not cover parts which may, under normal wear and tear, require replacement including, without limitation, tires, upholstery, fuses, etc.

TO THE EXTENT PERMITTED BY APPLICABLE LAW, PROBITY CELL IS NOT LIABLE FOR ANY DIRECT, INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR SERVICE OF THE SNAPnGO. THE WARRANTY AND REMEDIES STATED ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, REMEDIES OR CONDITIONS, WHETHER ORAL, WRITTEN, EXPRESS, STATUTORY, OR IMPLIED TO THE EXTENT PERMITTED BY APPLICABLE LAW. PROBITY CELL SPECIFICALLY DISCLAIMS ALL IMPLIED AND STATUTORY WARRANTIES INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IF IMPLIED WARRANTIES CANNOT BE DISCLAIMED, SUCH WARRANTIES ARE LIMITED IN DURATION TO THE DURATION OF THIS WARRANTY. Any recovery is limited to the original purchase price. No person is authorized to modify this Limited Warranty.

THIS WARRANTY DOES NOT AFFECT YOUR STATUTORY RIGHTS.

Some states do not allow limitations on how long an implied warranty lasts, or exclusions of incidental or consequential damages and the above limitations may not apply to you. This Limited Warranty gives you specific legal rights. You may have other rights, which vary from state to state.

This warranty and all lawsuits, disputes, and claims will be governed by and interpreted under the laws of the State of Nebraska, regardless of any conflict of law principles. The parties also irrevocably consent to the jurisdiction of the District Court of Phelps County, Nebraska, and agree that the District Court of Phelps County, Nebraska shall have exclusive jurisdiction and be the sole venue for the consideration of any lawsuits, disputes, and claims between the parties.

The parties hereby waive the right to any jury trial on any lawsuit, dispute, claim, or controversy. The parties also waive any right to consolidate or to have handled as a class action any proceeding on any lawsuit, dispute, claim, or controversy. The parties agree that any proceedings will be conducted solely on an individual basis. The parties agree not to seek to have any lawsuit, dispute, claim, or controversy heard as a class action, private attorney general action, or in any other proceeding in which either party acts or proposes to act in a representative capacity.

If any provision herein is found to be illegal or unenforceable, that provision will be severed with the remaining in full force and effect.

YOUR INSURANCE POLICIES MAY NOT PROVIDE COVERAGE FOR ACCIDENTS INVOLVING THE USE OF THIS SCOOTER. TO DETERMINE IF COVERAGE IS PROVIDED, YOU SHOULD CONTACT YOUR INSURANCE COMPANY OR AGENT.